


AN ARRAY OF THERMAL TRANSFER RIBBON SOLUTIONS ■ ■ ■

Choose from three ribbon solutions to cover all your flexible packaging coding needs, whether basic or complex while guaranteeing you the best quality code, more production uptime and best-in-class Markem-Imaje service. All Markem-Imaje ribbons are designed, developed and tested with our SmartDate coders to offer you the best quality on the market.



SmartDate Xpert Ribbons

SmartDate Xpert Ribbons are full resin ribbons intended for your most demanding applications that require high levels of resistance to solvents, oil and heat.



SmartDate Xtra Ribbons

The SmartDate Xtra Ribbons raise the standards for thermal transfer coding. They offer a high level of versatility to code on most of your flexible packaging while ensuring durable codes from the production line until customer purchase.








SmartDate Xceed Ribbons

SmartDate Xceed Ribbons are the most cost-effective ribbons to secure your code, ensure readability and make the most of your SmartDate coders without compromising on quality.



RIBBON DISPOSAL

Component	 Re-usable	 Recyclable	 Incinerable	 Common Industrial Waste
TT Film	-	-	✓	✓
Plastic core	✓ as take-up core	✓ with same plastic type 	✓	✓
Roll packaging film	-	✓ with same type of plastics	✓	✓
Roll label	-	-	✓	✓
Cardboard box	✓	✓ with cardboard	✓	✓
Box label	-	-	✓	✓
Overpacking box	✓	✓ with cardboard	✓	✓
Pallet	✓	✓	✓	✓

CERTIFICATIONS*

- ▶ Food contact: 1935/2004/EC and FDA.
- ▶ Heavy metals: 2011/65/EC (RoHS).
- ▶ REACH: Ribbons are free from the Substances of Very High Concern (SVHC).
- ▶ California Proposition 65.

Contact us for all other regulations linked to product compliance with toxicity, waste treatment, banned components, packaging, etc.

* depending on grades

STORAGE AND USE

- ▶ Storage: 5-35 °C (40-95 °F), 20-80% humidity rate.
No shelf life in normal recommended storage conditions.
- ▶ Conditions of use:
Do not open with a blade.
Do not exert pressure on ribbon roll.
Before use, we recommend storing the ribbon at average temperature (20 °C) for 24 h.

SMARTDATE CODER COMPATIBILITY CHART

		SmartDate Xceed Ribbons			SmartDate Xtra Ribbons		SmartDate Xpert Ribbons		
		Black	White	Colours	Black	Metallic white	Black	White	Colors
SmartDate 2 Width (mm): 22 to 55	Length (m)	600	"-"	450	700	600	600	450	600
SmartDate 3 / 5 / X40 / X60 Width (mm): 22 to 55	Length (m)	900	650	800	1100	800	800	650	600
SmartDate X60-128 / SD5-128 Width (mm): 90 to 130	Length (m)	600	600	600	900	600	600	450	450
8018 Width (mm) : 22 and 33	Length (m)	500	300	400	550	400	400	400	400

We reserve the right to amend the design and/or specifications of our products without notice.

Markem-Imaje
Global Sales & Marketing Division
9, rue Gaspard Monge
B.P. 110
26501 Bourg-lès-Valence Cedex – France
Tél. : +33 (0) 4 75 75 55 00
Fax : +33 (0) 4 75 82 98 10



To learn more, visit www.markem-imaje.com